


# I34

## HIGHLY MOBILE COMPACT CRUSHER

The I34 compact impact crusher is the perfect solution for projects with small footprints but big requirements. These compact, mobile crushers are suited particularly to construction and demolition recycling, asphalt recycling, and aggregates.

This versatile, mobile crusher is able to nimbly move around in small spaces, and continue moving while crushing. The I34's small footprint is uniquely suited to the demolition and asphalt recycling, aggregates and smaller scale construction projects. Less than 2.5m wide, the crushers can be transported easily from site to site.


The new line boasts flexibility as well, not only can the I34 continue crushing while moving, it can convert to a recirculating impactor in just a few hours.



**LARGE FEEDER**  
Hardox® hopper with integral vibrating feeder. Feed rate is automatically controlled.

### DIRECT DRIVE CRUSHER

34 x 25.6" feed opening to new direct drive crusher more power, along with lower fuel costs.



**MAGNET**  
Reversible magnet enables material separation from the source material.

### RECIRCULATING SYSTEM

Recirculation conveyor allows operators to produce a crushed and screened final product with one machine.



Engine	252 Hp (188 kW) Diesel
Transport Height	9'-9" (2.982m)
Transport Length	30'-7" (9.315m)
Transport Width	8'-2" (2.486m)
Weight - w/ magnet & dirt conveyor	52,029lbs (23,600kg)
Crushing Chamber	860 x 650mm Opening
Rotor	900mm Diameter
Stockpile Height - Main Conveyor	9'-10" (3.01m)
Stockpile Height - Side Conveyor	8'-6" (2.58m)

# I34R

## RECIRCULATING COMPACT CRUSHER

The McCloskey I34R recirculating Impact Crusher combines the productivity of our I34 with the versatility of a full screening and recirculating system, allowing operators to produce a crushed and screened final product with one machine.

This versatile, mobile crusher is able to nimbly move around in small spaces, and continue moving while crushing. The I34R's small footprint is uniquely suited to the demolition and asphalt recycling, aggregates and smaller scale construction projects. Less than 2.5m wide, the crushers can be transported easily from site to site.

The new compact crushers boast flexibility as well, with standard machines converting to recirc in just a few hours.




**RADIAL RETURN CONVEYOR**  
Allows operators to recirculate oversized material from the screenbox back to the feed hopper or radial out up to 90° to feed another machine or stockpile up to 11' 9".

**SCREENBOX**  
High Energy Screenbox.



**LARGE FEEDER**  
Hardox® hopper with integral vibrating feeder. Feed rate is automatically controlled.

**DIRECT DRIVE CRUSHER**  
34 x 25.6" feed opening to new direct drive crusher more power, along with lower fuel costs.



**MAGNET**  
Reversible magnet enables material separation from the source material.



Engine	252 hp (188 kW) Diesel
Transport Height	10' (3.056m)
Transport Length	42' 9" (13.024m)
Transport Width	8' 4" (2.55m)
Weight (incl. magnet & dirt conveyor)	60,627 lb (27,500)
Stockpile Height - Fines Conveyor	8' 4" (2.54m)
Stockpile Height - Side Conveyor	8' 6" (2.58m)
Crushing Chamber	860 x 650mm Opening
Rotor	900mm Diameter
Screenbox Dimensions	2m x 1.1m