

## **SS-300**

SS-300

## TRACK SHREDDER

The ESS-300 is a tracked primary shredder capable of effectively and reliably shredding a wide range and type of material. The ESS-300 is designed to meet the needs of plants in which the incoming materials vary greatly in terms of size, composition, and difficulty to shred.

The interaction between the rotating knives on the single, hydraulically driven shaft ensures the input material is constantly moving to prevent bridging and maximizing shredding efficiency. The replaceable mesh setup allows the machine to perform to a number of different specifications of output material, with varying piece size. The quick change nature of these meshes is possible because of a side opening on the chamber which is opened and closed via a hydraulic cylinder.

## **FEATURES**

- Aggressive multi-tooth cutting shaft
- Intelligent electrical control unit
- Variable speed main conveyor
- 4 Meter tracks for superior maneuverability and stability.
- VOLVO D13 380kw (510HP) Stage V/Tier 4 Final
- Fuel efficient Hydraulics system
- User Friendly Hydraulic Controls
- Double Hydrostatic drive transmission



## **DIMENSIONS AND CAPACITIES**

LENGTH – WORKING (MAX)	15.64M (51'-4")	WIDTH – TRANSPORT	3.01M (9'-11")	AVERAGE FUEL CONSUMPTION	60 L/HOUR (15.5 US GAL)
HEIGHT – WORKING (MAX)	3.5M (11'-6")	HEIGHT – TRANSPORT	3.69M (12'-2")	MACHINE WEIGHT	35,000KG (77,160 LBS.)
LENGTH – TRANSPORT	9.94M (32'-7")	MAXIMUM PRODUCTION RATE	60 TPH (MATERIAL DEPENDENT)		

© Copyright 2021 McCloskey Environmental. All rights reserved. McCloskey is a trademark of McCloskey International.

McCloskey Environmental reserves the right to make changes to the information and design of the machines on this brochure without reservation and notification to the users. Information at time of print considered accurate – McCloskey Environmental assumes no liability resulting from errors or omissions in this document.